Corning Incorporated Life Sciences

Registered ISO 9001:2008

Product Description

Catalog Number: 3599

Product Description: Costar ® 96-well cell culture multiple well plate, flat bottom, with lid

Component Materials:

Plate/Lid - Virgin Polystyrene, meets USP, Class VI requirements for plastic containers and

closures

Product Dimensions:

Length of Plate - 5.030 in. Diameter of Well @ top - .270 in. Width of Plate - 3.365 in. Diameter of Well @ - .250 in.

bottom

Depth of Well - .420 in. Height with Lid - .650 in.

Tolerances of - +/-.010 in. Working Volume per well - 0.1 - 0.2 mL

Dimensions

Sterilization:

The product is irradiated and dosimetrically released based on ANSI/AAMI/ISO 11137 *Sterilization of healthcare products-Requirements for validation and routine control-Radiation sterilization.*Sterility Assurance Level: SAL 10⁻³

Pyrogens:

The product has been tested and has met the criteria established in the current version of ANSI/AAMI ST 72:2002/(R)2010 Bacterial Endotoxins - Test methodologies, routine monitoring, and alternative to batch testing. Results: ≤ 0.1 EU/mL (≤ 4EU/device)

Surface Characterization:

Surface is characterized to be hydrophilic and negatively charged, composed of 9-17% oxygen atoms. This surface composition has been optimized for cell attachment and growth.

Cell Attachment and Growth Characteristics:

The product has been tested for the attribute of cell attachment and growth utilizing an attachment- dependent mammalian cell line in a serum supplemented media.

Bovine Spongiform Encephalopathy and Transmissible Spongiform Encephalopathy:

This product does not contain materials of animal origin.

Performance Testing:

Each manufacturing lot is sampled and tested in accordance with Standard Operating Procedures.

Cell Culture Treatment: Wettability test using water to insure the presence of a hydrophilic

surface.

Visual Attributes: Visual and microscopic examination of the product.

Packaging: Inspection for seal and barrier integrity, accurate labeling, and correct

product configuration.

Lot Number Designation:

8 Digit Lot Number: First 3 digits - Julian date, start of manufacturing; Next 2 digits - Year of manufacture; Last 3 digits - Batch identification.

Rev No: 14