Corning Incorporated Life Sciences

Registered ISO 9001:2008

Product Description

3494 Catalog Number:

Product Description: Costar® Transwell-COL®, 12mm, 3.0 µm pore size

Component Materials:

Plate/Lid Virgin Polystyrene, meets USP, Class VI requirements for plastic containers and

closures.

Transwell body Virgin Polystyrene, meets USP, Class VI requirements for plastic containers and

closures.

Filter Transparent collagen-treated PTFE membrane.

Types I and III bovine placentae Collagen

Product Dimensions:

Length of Plate 5.035 in. Bottom of Transwell to .040 in.

plate

Width of Plate 3.370 in. Volume added / plate 1.5 mL Height with Lid .890 in.

Volume added / 0.5 mL

Transwell

Tolerances of +/-.050 in.

Dimensions

Sterilization:

The Transwells are sterilized according to ANSI/AAMI/ISO 11135 Medical Devices - Validation and routine control of ethylene oxide sterilization and released after successful sterility testing of Biological Indicators. Sterility Assurance Level: SAL 10-6 The plates are irradiated and dosimetrically released based on ANSI/AAMI/ISO 11137 Sterilization of healthcare products-Requirements for validation and routine control-Radiation sterilization. Sterility Assurance Level: SAL 10⁻³

Cell Attachment and Growth Characteristics:

The lot has been tested for the attribute of cell attachment and growth utilizing an attachment-dependent mammalian cell line in a serum supplemented media.

Performance Testing:

Each manufacturing lot is sampled and tested in accordance with Standard Operating Procedures.

Visual and microscopic examination of the product. Visual Attributes:

Packaging: Inspection for seal and barrier integrity, accurate labeling, and correct

product configuration.

Colormetric determination of collagen attachment to the membrane. Collagen Assay: Cell Attachment/Growth: Four to five day cell attachment and growth to \geq 95% confluency.

Lot Number Designation:

8 Digit Lot Number: First 3 digits - Julian date, start of manufacturing; Next 2 digits - Year of manufacture; Last 3 digits - Batch identification.

Rev No: 5